B4-C

FRP COMPOSITE MAINTENANCE PLATFORMS

B4 Platform height: 42" - 84" (1.07m-2.13m)

FRP Composite main construction- lightweight, non-conductive, and corrosion proof with a UV-resistant surface veil

Powder-coated finish on all steel componentscustom colors available

Easy to operate, high-capacity manual hydraulic hand pump

3' x 7' (.91m - 2.13m) platform area

750 lbs. (340.19 kg) max load capacity

Removable FRP composite handrails and safety chain across access side

Onboard storage hooks for railings when not in

6" (15.24 cm) locking swivel casters with independent brakes and swivel locks

Steel tow bar with pintle eye, locks in the upright position when not in use

FRP deck with gritted- non-slip surface

Front side bumper for aircraft protection

Platform locking pins for additional safety, spaced for 6" height adjustments

Telescoping FRP composite ladder allows access at any height

Wide, stable base footprint

Compact shipping footprint for low cost transport- these stands can also be shipped broken down for on-site assembly as a kit, providing reduced shipping costs

Hand pump controls and locking pins relocated to be operable from ground level to meet new AFMAN 91-203 standards (16.5.4.6 and 16.5.11.4)







PLATFORM HEIGHT RANGE	42"-84" (1.07m-2.13m)
PLATFORM AREA	36" x 84" (0.91m x 2.13m)
BASE DIMENSIONS	50-3/4" x 88-3/8" (1.29m x 2.25m)
UNIT WEIGHT	580 lbs. (263kg)

APPLICABLE OSHA STANDARDS MET:

1910.23(1)(e)

1910.23(2)

1910.23(3)



APPLICABLE AFMAN 91-203 STANDARDS MET:

7.1.4.1

7.1.5.1

7.1.5.5

7.1.6

16.5.1

16.5.2.1

16.5.2.2

16.5.2.2.1

16.5.2.3

16.5.2.4

16.5.2.5

16.5.3.1

16.5.3.2

16.5.3.4

16.5.4.6

16.5.5

16.5.9

16.5.10

16.5.11



13733 West Rena Dr. Largo, FL 33771 (904)-8-STRONG (904)-878-7664

(904)-878-7664 === www.fiber-strong.com email: sales@fiber-strong.com

