



# ***TW3025***



# ***TW3025***

## ***Specifications:***

Length:	28'	
Height:	96" (Stowed)	
Width:	72"	
Weight:	30x Series Aluminum Frame Ramp:	1,450 lbs
	30x Series Aluminum Frame W/ Canopy option Ramp:	1,950 lbs
Wheels:	All pneumatic, industrial foam filled.	
Surface:	36" Wide Adhesive Anti-Slip	
Range:	Lowest setting 43", Highest setting 77"	
Brake:	Dead Man style	
Provided	Tow Bar, Wheel Chocks	
Canopy:	Optional and has capability to fit over fuselage of any Aircraft in the above range. Ramps with the optional canopy are built with additional weight and outriggers for wind stability.	
Training:	Onsite and included in price.	
Warranty:	2-year warranty on manufacturing or material defects. 5 year warranty on Safeguard Anti-Slip walking surface.	
Degree of Slope:	Varies with aircraft; from 10 degrees but not to exceed 14 degrees as per AC 150/5220-21C.	

Standard Ramp meets 90 MPH FAA requirement when stowed.

One man operation.

Deployed in less than one minute with trained individual.

The Turboway passenger ramp is a universal ramp designed to serve commuter size aircraft. This ramp allows easier access for all passengers, disabled, and non-disabled. With its adjustable slope and pivoting bridge; it lays over existing aircraft stairs and provides a faster, safer, and more comfortable alternative to boarding and deplaning. The Turboway is comfortably sloped, non-motorized, and easy to operate.

**This ramp can be used on all aircraft  
ranging in height from a Metro to a CRJ900/1000.**