PREMIUM TRUCK SCISSOR DOCK LIFT - WL-100-6-610

ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE
ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE
DIMENSIONS WITH YOUR SALESPERSON

STANDARD FEATURES	WITH YOUR SALESPERSON
	120"
MODEL NUMBER: WL-100-6-610	OVERALL LENGTH
UNIT TO BE MOUNTED: AT SURFACE	OVERALE LENGTH
OR IN PIT (CIRCLE ONE) CAPACITY (EVENLY DISTRIBUTED):	
6,000 LBS	
OVERALL PLATFORM SIZE:(72" X 120")	ソソソソソソソソソソガベイー
RAISED HEIGHT 70" ± 2"	
LOWERED HEIGHT: 10"	USEABLE WIDTH= 72"X 18"
REMOVABLE HANDRAILS AND 4"NON-	
REMOVABLE TOE BOARDS 45" HT W/ 72"	
21" MID-RAIL OVERALL	
TRUCK BRIDGE IS 72" W X 18" L AT WIDTH	AND NON-REMOVABLE TOE BOARDS
ROLLER END W/ CHAINS & HANDLES	\/\/\/\/\/\/\/\/\/\/\/\/\/\/\/\/\/\/\/
FRAME SIZE IS: 62" W X 118" L	/\/\/\/\/\/\/\/\/\/\/\/\/\/\/\/\/\/\/\
SHIPPING WT APPROX: 3500 LBS ±	ンンソンソンソンソンメバリー
6 1/2 HP POWER UNIT (SEE BOTTOM	
OF PAGE)	
	** STANDARD UNIT NOT INTENDED FOR SIDE CROSS LOAD **
-HAND-HELD CONTROL ON A	
4'-20' COIL CORD	
REFER TO THE UNIT'S ELECTRICAL	
DIAGRAM FOR	(Þ │
ELECTRICAL SERVICE	
REQUIREMENTS	0
-INSTALL TO MEET ALL APPLICABLE	
STATE & LOCAL	
CODES FOR YOUR AREA!	
5" BEVELED TOE GUARD	
ARCHITECTURAL REVIEW FOR	
CONNECTIVESS OF FIT AND FOR	
COMPLIANCE TO LOCAL AND STATE CODES IS RECOMMENDED.	
70"	
RAISED	
HEIGHT	□
I 10"	
DIMENSION TOLERANCE ± 1/4" LOWERED—	
HEIGHT	H-6
SPECIAL FEATURES	**************************************
NONE	
	SAFETY MAINTENANCE PROPS
EOD INTERNAL LISE ONLY	
FOR INTERNAL USE ONLY PROJECT SIGN OFF	REPRESENTED SATISFIES DESIGN AND DIMENSION
SALES	REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO
	P CONFIRM PRODUCT AND INSTALLATION
ENG.	COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.
FAB.	ANY MODIFIED UNITS ARE NON-RETURNABLE
POWER	0 1 As drawn 1 1 As marked
	V
HYDRAULIC UNIT OVERALL DIMENSIONS	A Signed:Date:
14"W x 33"L x 31"H	L Printed Name:
(COMES W/ 8FT HOSE)	LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING
POWER AC DC (12V) AIR/OIL	DISTRIBUTOR'S NAME: P.O.# X
FOWER AC DC (124) AIR/OIL	
MOTOR VOLTAGE 115 208 230 460	W.O.# X
DEDICATED CIRCUIT REQUIRED 60Hz	DRAWN BY: DLS DATE: 8/1/2016 SALES: X
	DLS 8/1/2016 X
MOTOR PHASE SINGLE THREE	REFERENCE: X SCALE: 1:36 FILE NAME:
CONTROL HAND FOOT	QUOTED LEAD TIME: X QUOTE # 05-007-310